





Application

Can not be used for pre-wall installation systems Slim For touchless flushing with a sensor

For pre-wall installation systems and concealed WC cisterns

Features

- Magnetic switch for service setting and cleaning
- Material: plastic
- Option to use the button for a large flush
- Powered by the main electric supply, the power source must be purchased (12 V DC min 1 A) - recommended AEZ310
- Setting via mini USB using free software available on the Alcaplast website
- Adjustable parameters: start and end time of registration, duration of flushing, automatic flush, allowing flooding, flooding time, variable settings hygienic rinse

Scope of supply

- Infrared sensor
- Connector for attaching to the source
- Screw set with a solenoid valve
- Flush plate
- Fixing frame of the flush plate
- Flush valve for sensor flushing
- Threaded frame clamp 2 pcs

Order number, Logistic information

Code	EAN	(kus packing palett)	(piece packing)	(packing palett)
M370S	8595580501709	1,5275 15,2750 264,4000 kg	315×210×120 595×395×435 mm	10 160 pcs
		1,52,53 13,2,550 201,1000 kg	515X216X126 555X655X1551111	10 100 pes

Guarantee **Customs code** 2/2 years 84818019 EN 55014, EN 55022, EN 61000

Technical specifications

- Operating force < 20 N
- Power consumption 8,5 W
- Output voltage 12 V DC