



M371SB

Flush plate with sensor for pre-wall installation systems, chrome-polished (DC battery operated)





Application

Can not be used for pre-wall installation systems Slim For touchless flushing with a sensor

For pre-wall installation systems and concealed WC cisterns

Features

- Magnetic switch for service setting and cleaning
- Material: plastic
- Option to use the button for a large flush
- Battery power is included in packaging
- Setting via mini USB using free software available on the Alcaplast website
- Adjustable parameters: start and end time of registration, duration of flushing,
- automatic flush, allowing flooding, flooding time, variable settings hygienic rinse Surface finish: chrome-polished

Scope of supply

- Infrared sensor
- Connector for attaching to the battery
- Case for alc. batteries 6V
- Screw set with a solenoid valve
- Flush plate
- Fixing frame of the flush plate
- Flush valve for sensor flushingThreaded frame clamp 2 pcs

Order number Logistic information

order number, Edgistic information				
		Weight	Dimensions	Quantity
Code	EAN	(kus packing palett)	(piece packing)	(packing palett)
M371SB	8595580530808	2,4980 2,4970 419,6800 kg	315×210×120 315×120×210 mm	10 160 pcs
Guarantee	Customs code Norms			

2/2 years 84818019 EN 55014, EN 55022, EN 61000

Technical specifications

- Operating force < 20 N</p>
- Power consumption 8,5 W
- Output voltage 6 V